

ROOF VENTILATORS

Characteristics

- As a Korea's first AMCA (Air Movement and Control Association) certified product, excellence in performance verified
- Light weight and durable structure achieved by the use of aluminum
- Possible to select from two options : Belt approach or Direct-drive approach
- Customized design available in accordance to the area of installation
- As a power fan, high performance achieved and level of noise lowered by screen door installed inside



Product data

MOTOR	Rotative speed	Static Pressure (Pa)									
		0	49	98	147	196	245	294	343	392	
HP	RPM										
1/2	400	m³/min	54.5	28.0							
		BHP	0.07	0.07							
		dB(A)	59	58							
	600	m³/min	81.8	69.8	51.0						
		BHP	0.22	0.24	0.23						
		dB(A)	70	69	68						
1	800	m³/min	109.1	101.0	90.7	77.1	56.1				
		BHP	0.5	0.5	0.56	0.56	0.51				
		dB(A)	78	77	76	76	75				
1.5	1000	m³/min	136.4	130.7	123.0	114.4	104.1	92.8	77.8		
		BHP	1.00	1.03	1.06	1.09	1.09	1.08	1.03		
		dB(A)	84	83	82	82	81	81	81		
2	1170	m³/min	159.5	155.3	148.9	142.0	134.6	126.0	116.8	106.8	94.6
		BHP	1.59	1.62	1.67	1.70	1.73	1.74	1.74	1.72	1.67
		dB(A)	88	87	87	86	86	85	85	84	83

• KRF-022BH

